



**Product**

**Part No.**

**Qty Req**

**FRONT SUSPENSION**

**SHOCK ABSORBER**

Nitro Gas Strut			<b>12713GR</b>	2
Foam Cell Strut			<b>24713FE</b>	2

**COIL SPRINGS**

	<b>Estimated Lift</b>	<b>Additional Load</b>		
Performance	40mm	0 - 50kg	<b>MITS038B</b>	1
Constant Load or Diesel	40mm	50 - 100kg	<b>MITS038C</b>	1

**REAR SUSPENSION**

**SHOCK ABSORBER**

Nitro Gas			<b>12714GR</b>	2
-----------	--	--	----------------	---

**COIL SPRINGS**

	<b>Estimated Lift</b>	<b>Additional Load</b>		
Performance SWB	40mm	0 - 200kg	<b>MITS039A</b>	1
Performance LWB	40mm	0 - 200kg	<b>MITS039B</b>	1
Constant Load	40mm	200kg - GVM	<b>MITS039C</b>	1

**SUSPENSION KIT**

Performance SWB w/ Gas Shocks	<b>MITS038AKG</b>
Performance LWB Petrol w/ Gas Shocks	<b>MITS038BKG</b>
Performance LWB Diesel w/ Gas Shocks	<b>MITS038CKG</b>
Constant Load LWB Petrol w/ Gas Shocks	<b>MITS038CKG1</b>
Constant Load LWB Diesel w/ Gas Shocks	<b>MITS038CKG2</b>

- Vehicles with Monocoque body construction can be subject to increased NVH (Noise) with upgraded suspension installed
- Vehicles with independent suspension must maintain a minimum of 60mm downward suspension travel
- Mandatory 4 wheel alignment after installing new suspension

**SUSPENSION KIT CONTENTS**

Shock Absorbers	Coil Springs
Strut Shock Absorbers	